

公司总部及各办事处联系方式

中国华南研发制造基地

广东拓斯达科技股份有限公司

地址：广东省东莞市大岭山镇大塘朗创新路2号

电话：86-769-8305 0999

传真：86-769-8584 5562

邮箱：marketing@topstarltd.com

South China R&D and Manufacturing Base

Guangdong Topstar Technology Co., Ltd.

ADD : No.2 Chuangxin Road, Datanglang, Dalingshan Town, Dongguan City, Guangdong Province.

TEL: 0086 769 8305 0999

FAX: 0086 769 8584 5562

E-mail:marketing@topstarltd.com

中国华东研发制造基地

江苏拓斯达机器人有限公司

地址：江苏省苏州市吴中经济开发区郭巷街道淞葭路1999号

电话：0512-8686 4305

手机：185 0156 0757

East China R&D and Manufacturing Base

Jiangsu Topstar Robot Co., Ltd.

ADD: No.1999 Songjia Road, Guoxiang Street, Wuzhong Economic Development Zone, Suzhou City, Jiangsu Province

TEL: 0512-8686 4305

MOB: 185 0156 0757

苏州拓斯达智能装备有限公司

地址：江苏省苏州市吴中经济开发区郭巷街道淞葭路1999号C栋1楼

电话：0512-5288 9310

手机：185 0156 0757

Suzhou Topstar Intelligent Equipment Co., Ltd.

ADD: 1F, Building C, No.1999 Songjia Road, Guoxiang Street, Wuzhong Economic Development Zone, Suzhou City, Jiangsu Province

TEL: 0512-5288 9310

MOB: 185 0156 0757

宁波拓晨机器人科技有限公司

地址：浙江省余姚市凤山街道舜汇东路93弄

电话：86-574- 8610 5571

传真：86-574- 8610 5571

手机：137 7723 2779

Ningbo Topstar Robot Technology Co., Ltd.

ADD: Lane 93, Shunhui East Road, Fengshan Street, Yuyao City, Zhejiang Province

TEL: 86-574-8610 5571

FAX: 86-574-8610 5571

MOB: 137 7723 2779

华中服务办事处

地址：重庆市渝北区融创中央广场5栋1105室
手机：186 0209 6012

Central China Service Offices,China
ADD: Room 1105, Building 5, Rongchuang Central Plaza, Yubei District, Chongqing
MOB: 186 0209 6012

华北服务办事处

地址：天津市西青区精武镇才智道12号德维洛浦产业园C座4-2-3
手机：139 2957 0939

North China Service Offices,China
ADD: 4-2-3, Block C, Deweiliuopu Industrial Park, No.12 Caizhi Road, Jingwu Town, Xiqing District, Tianjin
MOB: 139 2957 0939

越南服务办事处

地址：北江市黎利坊雄王路3号TUTACENTER 一楼
手机：186 0209 6307 / 0084-346 860 156

Vietnam Service Office
Address: 1st Floor, TUTACENTER, No. 3, Xiongwang Road, Lilifang, Bac Giang
MOB: 186 0209 6307 / 0084-346 860 156

有关产品性质和适用范围的说明并不保证产品属性，仅作可供了解的信息。我们的供货范围及提供的服务完全以合同条款为准绳。技术数据和插图仅作为供货参考。保留更改权利。

Feature and scope of the product does not guarantee the product attributes,only for reference.Our scope of delivery and services provided are based solely on the terms of delivery and services provided are based solely on the terms of the contract.Technical data and illustration are only for reference .We reserve the rights of changing.



全国统一客服热线
Domestic Service Hotline
400-096-8005
Http://www.topstarltd.com

TSDSC2023-A



TS系列注塑机

TS SERIES INJECTION MOLDING MACHINE

机铰式液压伺服驱动
Toggle Hydraulic Servo Driven



股票代码 Stock Code 300607

CONTENTS

目录

01 公司介绍

About Us

公司简介	01-02
Company profile	
企业文化	03-03
Company Culture	
资质评定	04-04
Qualification evaluation	
发展历程	05-06
Development History	

02 产品介绍

Product Introduction

事业部介绍	07-08
Business Unit Introduction	
产品介绍	09-09
Product Introduction	
应用行业	10-10
Application industries	
产品配件	11-11
Product accessories	
产品特点	12-12
Product Features	
产品参数	13-15
Product Parameters	
产品规格	16-17
Product Specification	
产品安装尺寸	18-18
installation dimensions	
标准系列配置表	19-20
Standard series configuration table	

03 客户服务

Chapter of Service

售后服务	21-21
After-Sale Service	
全球服务网点	22-22
Global Service Net	



COMPANY PROFILE

公司简介

广东拓斯达科技股份有限公司（简称：拓斯达，股票代码：300607）成立于2007年，总部位于广东省东莞市大岭山镇，注册资本4.26亿元。

拓斯达坚持“让工业制造更美好”的企业使命，通过以工业机器人、注塑机、CNC为核心的智能装备，以及控制、伺服、视觉三大核心技术，打造以核心技术驱动的智能硬件平台，为制造企业提供智能工厂整体解决方案。截至2023年01月，公司已在全国设有近40家办事处，触达客户超20万家，服务客户超15000家。

Guangdong Topstar Technology Co., Ltd. (abbr. Topstar, stock code: 300607) was established in 2007 and headquartered in Dalingshan Town, Dongguan City, Guangdong Province with a registered capital of 426 million yuan.

Topstar insists on the corporate mission of "making industrial manufacturing better". Through industrial robots, injection molding machines, CNC as the core of intelligent equipment and controllers, servo drives, and vision system as three core technologies, to create a core technology-driven intelligent hardware platform for manufacturing enterprises to provide intelligent factory solutions. As of January 2023, the company has set up nearly 40 offices across the country, reaching more than 200,000 customers and serving more than 15,000 customers.

注册资本
Registered Capital **4.26** 亿元

办事处近
Offices **40** 家

服务客户超
Serving Customers **15000** 家

授权专利
Patents **672** 项

软件著作权
Software Copyright **77** 项

研发技术人员近
R&D Technicians **1000** 人

公司是国家高新技术企业、广东省机器人骨干企业、广东省服务型制造示范企业、东莞市“倍增计划”试点企业，建有广东省企业重点实验室、广东省工程技术研究中心、广东省企业技术中心、广东省博士工作站、东莞市技师工作站等人才及科研平台。公司荣获“东莞市政府质量奖”“东莞市先进集体”“东莞市友善企业”等奖项，并入选“2021中国智能制造50强”“2021广东企业500强”“2021工业机器人TOP50”等榜单。

截至2023年01月，拓斯达拥有授权专利672项，其中发明专利88项；各类软件著作权77项。公司多项产品荣获广东省名牌产品、广东省名优高新技术产品，并通过欧洲CE认证。

Topstar is a National High-Tech Enterprise, Guangdong Province Robot Backbone Enterprise, Guangdong Province Service-oriented Manufacturing Demonstration Enterprise, and Dongguan Doubling Plan Enterprise. We have built key laboratories in Guangdong Province, Guangdong Engineering Technology Research Center, Guangdong Enterprise Technology Center, Guangdong Doctoral Workstation, Dongguan Technician Workstation, and other talents and scientific research platforms. Topstar won the "Dongguan Government Quality Award", "Dongguan Advanced Collective", "Dongguan Friendly Enterprise", and other awards. And it was selected in the "Top 50 Intelligent Manufacturing in China in 2021", "Top 500 Guangdong Enterprises in 2021", "Top 50 Industrial Robots in 2021", and other lists.

As of January 2023, Topstar has 672 authorized patents, including 88 invention patents; 77 software copyrights of various types. Many of our products have won the Guangdong Famous Brand Products, and Guangdong Famous High-tech Products, and passed the European CE certification.

Company Culture

企业文化

企业使命

Enterprise Mission

让工业制造更美好

Make Industrial Manufacturing Better

企业定位

Enterprise Positioning

以核心技术驱动的智能硬件平台

Intelligent hardware platform driven by core technology

企业愿景

Enterprise Vision

助力100万制造企业实现智能制造

助力100万工程师服务于智能制造

To help millions of manufacturing enterprises to realize intelligent manufacture
To help millions of engineers serving the intelligent manufacture

核心价值观

Core Values

全心全意为客户服务

群体奋斗，群体成功

Wholeheartedly for Customer Service
Together We Strive,Together We Achieve

组织气质

Team Spirit

开放协同，因我不同

Cooperate but respect personality

拓斯达不是雇佣和解雇型企业，而是打造创业型平台，集众人之力，实现凭一己之力所无法达成目的的平台，其核心精神是"分享"。——《拓斯达宣言》
TOPSTAR is not a hiring or dismissal enterprise, but aim to create a business platform, which setting the power of everyone to achieve the goal which can not be achieved by their own. Its core spirit is "share".



Qualification Evaluation

资质评定

拓斯达坚持技术为王的经营理念，先后取得了各项高新技术企业的资质和认证，为客户提供先进和高端的产品。

Topstar adheres to the bussiness philosophy,which puts technology in the dominant position. It has successively obtained many qualifications and certifications of high-tech enterprises, and provided the most advan and high-end product to customers.

国家级高新技术企业认证、欧盟CE认证、ISO9001质量体系认证、广东省名牌机器人、广东省“守合同重信用”企业、粤港澳大湾区联合创新中心创新基地、累计产品技术专利464项、广东省级企业技术中心、华南理工大学产学研合作基地、校企合作实践基地....

National high-tech enterprise certification、CE Certification、ISO9001 Quality System Certification、Guangdong Province Top Brand Robot、Guangdong Province "contracts observing and credit honoring" enterprises、Guangdong-Hong Kong-Macao Greater Bay Area Joint Innovation Center、464 technology patenes for products、Guangdong province enterprise technology center、South China University of technology production and research cooperation base、School-enterprise cooperation practice base....





苏州吴中经济开发区——华东研发制造基地
Suzhou Wuzhong Economic Development Zone – East China R&D and Manufacturing Base

Introduction of Injection Molding Machine Business Unit

注塑机事业部介绍

让注塑制造更高效，让工业制造更美好

Make injection molding manufacturing more efficient, make industrial manufacturing better

拓斯达注塑机事业部是国内唯一拥有注塑机到辅机全套设备自主研发产体系的注塑装备机构，具有自研率高、用户群广、集成经验丰富、可整厂实施四大优势。

坚持“让工业制造更美好”的使命，立足于拓斯达智能装备平台，汇聚30余年品牌的注塑机传承，致力推进注塑机和注塑系统工程更智能，为客户提供注塑全流程、全周期产品服务。

Topstar Injection Molding Machine Business Unit is the only domestic injection molding equipment organization with an "injection molding machine and auxiliary equipment self-research and self-production system". Its advantages are high self-research rate, wide user base, integration experience and implementation of the whole plant.

Topstar insists on the mission of "making industrial manufacturing better". Based on the Topstar intelligent equipment platform and more than 30 years of brand injection molding machine heritage, we are committed to promoting more intelligent injection molding machines and system engineering, to provide customers with the whole process and the whole cycle of injection molding product services.

研发理念

R&D Concept

拓斯达注塑机研发理念聚焦“系统化、通用化、精密化、性价比”。Topstar injection molding machine research and development concept focus on "systematization, universalization, precision, cost-effectiveness".

系统化是指通过硬件注塑机机械手辅机的配合，实现如“机械手跟踪锁模位置补偿”提高注塑工作站性能，通过软件注塑机控制系统实现注塑机辅机一体化控制，形成注塑行业系统化整体解决方案。

Systematization refers to the use of hardware to enable the injection molding machine, robot and auxiliary machine to cooperate to achieve "robot tracking clamping position compensation" and improve the performance of the injection molding station. At the same time, the use of "injection molding machine control system" software to achieve the integration of injection molding machine and auxiliary machine control, thus forming a systemic overall solution for the injection molding industry.

通用化是指拓斯达注塑机面向大多数行业，增加注塑机应用的场景，为客户多种类产品生产提供便利。

Generalization means that the Topstar injection molding machine applies to most industries and scenarios of injection molding machine applications, and it can facilitate the production of many kinds of products for customers.

精密化是指通过自主研发，不断优化产品设计，提升温度、速度、注射压力、降低原料及能源消耗等关键指标控制，提升制品质量及生产效益。

Precision refers to the optimization of independent research and product design to improve temperature, speed, injection pressure; reduce raw materials; control energy consumption and other key indicators, to improve product quality and production efficiency.

性价比则满足与相同价位产品，实现在配件、功能上提升10%–15%的设计原则，为客户提效降本。

Cost-effectiveness refers to the design principle of "10%–15% improvement in accessories and functions of injection molding equipment" when comparing with products of the same price level, to improve efficiency and reduce costs for customers.

TS Series Products

TS 系列产品

注塑机具有能一次成型外型复杂、尺寸精确或带有金属嵌件的质地密致的塑料制品的能力。
The injection molding machine has the ability to mold dense plastic products with complex appearance, precise dimensions or metal inserts in one go.

产品特点

Product Features



- 高强度，稳定可靠
- 优良塑化组件
- 高稳定，精密控制
- 高端、自研、12寸屏电脑
- 宁静节能

Application Industries

应用行业

电子类
Electronics

容器类
Containers

3C家电
3C Home Appliances

化妆品
Cosmetics

汽配行业
Auto Parts

日用品
Daily Products


Product Accessories

产品配件


TS 通用型精密伺服注塑机 90T-470T
TS general-purpose precision servo-driven injection molding machine 90T-470T



先进的油路设计，搭配专业控制器，使得机器动作稳定、制品良率高、响应速度快、控制精准、操作简单，满足多种工艺需求。
Advanced oil circuit design with professional controller makes the machine action stable, combined with high product yield, fast response time, precise control, easy operation, and meet a variety of process requirements.



采用斜排双射移油缸及线性导轨，射胶更加精准稳定。
Diagonal double injection mold shift oil cylinder and linear guide, more accurate and stable injection.



模板优化升级，结构可靠，变形小，能有效保护设备，提高模具使用寿命。
Optimized and upgraded platen, with reliable structure and small deformation, can effectively protect the equipment and improve the service life of mold.




标准螺杆：高性能氮化钢，耐用高效，应用广。
高混色/高混炼螺杆：满足高混色制品，易换色定制螺杆；不同制品特别定制塑化组件，如PC、PA等。
Standard screw: high performance nitride steel, durable and efficient, wide application High color mixing/high mixing screw: to meet the high color mixing products, easy to change color custom screw: specially customized plasticizing components for different products, such as PC, PA, etc.

Product Features


产品特点



先进的射胶、锁模、油压系统设计，机器参数全面升级；
Advanced design of injection, mold clamping and oil pressure system, and comprehensive;



全新斜排机铰布局，可实现超长行程开模，开模位置精度<1mm，模板运动快且稳；
Brand new diagonal hinge layout, which can realize ultra-long stroke mold opening, mold opening position accuracy <1mm, fast and stable platen movement;



采用独特的双滑脚设计，模板平行度调节方便；
Unique double slider design, easy to adjust the parallelism of the platen;




采用欧标顶针，顶针操作空间大；
European standard ejector pin, with large operation space;



全新的调模机构，一键即可实现自动精准调模；
New mold adjustment mechanism, with one-key function available to realize automatic and accurate mold adjustment;



双射移搭配线性导轨，射台运动阻力小，动作灵敏，射胶精准稳定；
Double injection shift with linear guide, low resistance of injection unit movement, sensitive action, accurate and stable injection;



射胶传动轴采用三轴承设计，保证同轴度，螺杆料筒磨损小；
Three bearing design for the injection drive shaft to ensure coaxiality and small wear of the screw barrel;




油路系统全面升级，安全，稳定，功能全，差动锁模运行周期快；
Oil circuit system fully upgraded, safe, stable, full-featured, with fast operation cycle of differential clamping;



采用高端注塑机专业电脑控制器。
High-end injection molding machine professional computer controller.

Product Specification

产品规格



TS90-TS330 外观尺寸图
TS90-TS330 Appearance size chart

外观尺寸

	TS90	TS130	TS170	TS220	TS260	TS330
a1	80	80	80	80	80	105
a2	791	791	891	1069	1145	1460
a3	784	884	1013	1046	1140	1150
a4	1910	1940	2020	—	—	—
a5	—	—	—	1015	1075	1525
a6	—	—	—	1135	1135	1310
b1	1603	1764	1836	1894	2037	2520
b2	1343	1312	1459	1532	1553	1750
c1	674	714	782	835	945	1012
c2	3640	3770	4094	4420	4650	5645
c3	2375	2513	2805	3100	3392	3738
c4	4196	4428	4900	5429	5826	6704
c5	4456	4688	5180	5769	6166	7154
d1	272	307	342	387	430	502
d2	272	307	342	387	430	502
d3	586.5	611.5	651.5	743.5	783	865
d4	541.5	576.5	616.5	668.5	708	812
d5	655	690	730	784	824	990
d6	1241.5	1301.5	1381.5	1527.5	1607	1860

	TS90	TS130	TS170	TS220	TS260	TS330
h1	1600	1650	1725	1825	1947	2031.5
h2	1395	1415	1465	1505	1580	1660.5
h3	1840.5	1890.5	1965.5	2065.5	2187.5	2272
w1	720	790	870	978	1058	1200
w2	780	850	930	1038	1118	1280
w3	557	582	622	713.5	753.5	832
w4	512	547	587	638.5	678.5	787
w5	1045	1115	1195	1303	1383	1630
w6	590	590	590	590	640	590
s1	1160	1180	1220	1260	1320	1340
s2	1400	1455	1527.5	1605	1700	1785
s3	133	133	133	148	164.5	162
s4	1565	1615	1690	1790	1906.5	1997
m1	2225	2360	2640	2915	3200	3577

外观尺寸


	TS400	TS470
a1	100	105
a2	805	890
a3	805	890
a4	1490	1550
a5	645	730
a6	1100	1100
a7	1300	1300
b1	5300	5500
c1	1060	1140
c2	6670	6990
c3	4271.5	4666.5
c4	7305	7987
c5	7755	8437
d1	532	592
d2	532	592
d3	900.5	980
d4	820.5	880
d5	950	950
d6	1932	1932

	TS400	TS470
h1	1972	2027
h2	1877.5	1877.5
h3	2186	2251
w1	1284	1410
w2	1364	1490
w3	886.5	966.5
w4	806.5	866.5
w5	469.5	463
w6	495.5	501
w7	950	950
w8	590	590
s1	1340	1340
s2	1815	1875
s3	69	64
s4	1939	1994
m1	3995	4370

由于技术不断发展、设计的改进及更新，以上规格如有更改，恕不另行通知。
Due to the continuous development of technology, improvement and update of design, the above specifications are subject

Installation Dimensions

产品安装尺寸



TS400-TS470 外观尺寸图
TS400-TS470 Appearance size chart

机械手安装接口尺寸（注：A尺寸不含避震脚）
Robot assemble connecting size (Size A without level pad)

机型	TS90	TS130	TS170	TS220	TS260	TS330	TS400	TS470
A	1160	1180	1220	1260	1320	1340	1340	1340
B	272	302	337	382	422	495	530	590
C	133	133	133	148	164.5	162	69	64
D	360	410	455	510	570	670	710	810
E	525	550	590	682	722	804	839	908
F	480	515	555	607	646	751	759	908
G	50	50	50	50	70	70	75	75
H	70	90	90	90	90	160	80+80	100+100
I	270	270	270	270	270	420	420	480
L	M16	M16	M16	M16	M16	M20	M20	M20
M	160	160	160	195	196.5	222	127	127
N	6	6	6	6	6	6	9	9
P	165	160	162.5	185	206.5	212	124	124
Q	200	240	267.5	300	332.5	380	390	440
R	300	320	360	440	480	550	600	700
S	338	368	399	459.5	499	588.5	633.5	688.5

注塑机加料口安装尺寸
Installation size of injection molding machine filling port

机型	TS90	TS130	TS170	TS220	TS260	TS330	TS400	TS470
A	150	150	150	150	150	160	160	160
B	110	110	110	110	110	110	110	110
C	85	85	85	85	85	—	—	—
D	55	55	55	55	55	75	75	75
E	M10	M10	M10	M10	M10	M10	M10	M10
F	M8	M8	M8	M8	M8	—	—	—

Configuration Table of Standard Series

标准系列配置表

锁模部分 Mold Clamping		TS90	TS130	TS170	TS220	TS260	TS330	TS400	TS470
加大容量50/100/150mm	Increase mold capacity by 50/100/150mm	○	○	○	○	○	○	○	○
机铰用铜套	Bushes for Toggle	●	●	●	●	●	●	●	●
拉杆导套用含油铜套	Oiled bushes for tie bars	●	●	●	●	●	●	●	●
液压马达齿轮调模	Hydraulic gear pump for mold adjust	●	●	○	●	●	●	●	●
吊模架	Suspended formwork	○	○	○	○	○	○	○	○
油脂润滑(配自润滑轴承)	Grease lubrication (with self-lubricating bearing)	○	○	○	○	○	○	○	○
模具强制复位装置	Installation of forced reset device for mold	●	●	●	●	●	●	●	●
加装模具隔热板	Installation of heat insulation board for mold	○	○	○	○	○	○	○	○
弓形码模夹	Bow-shaped mold clamp	●	●	●	●	●	●	●	●
加装机械安全锁	Installation of mechanical safety lock	●	●	●	●	●	●	●	●
锁模导轨加装钢带	Installation of steel belt for mold locking guide rail	●	●	●	●	●	●	●	●
磁力模板	Magnetic template	○	○	○	○	○	○	○	○
模板增加T型槽+码模孔	Add T-groove + code mould hole for the template	○	○	○	○	○	●	●	●
模板增加T型槽	T-groove added for formwork	○	○	○	○	○	○	○	○
成品滑道	Finished slide	●	●	●	●	●	○	○	○

射胶部分 Glue Injectiont		TS90	TS130	TS170	TS220	TS260	TS330	TS400	TS470
加长射嘴50/100/150/200mm	Lengthen nozzle by 50/100/150/200mm	○	○	○	○	○	○	○	○
过滤网射嘴组件	Injection nozzle assembly of filter screen	○	○	○	○	○	○	○	○
弹簧自锁射嘴(国产)	Self-locking injection nozzle of spring (made in China)	○	○	○	○	○	○	○	○
混色混炼螺杆	Mixing screw with assorted color	○	○	○	○	○	○	○	○
PMMA塑化组件	PMMA plasticizing module	○	○	○	○	○	○	○	○
PC塑化组件	PC plasticizing module	○	○	○	○	○	○	○	○
软PVC塑化组件	Flexible PVC plasticizing module	○	○	○	○	○	○	○	○
加大一级熔胶马达	Upgrade glue melting motor by a grade	○	○	○	○	○	○	○	○
减小一级/二级射胶机构	Degrade glue injection mechanism by a/two grade	○	○	○	○	○	○	○	○
射台加装手动润滑泵	Install manual lubrication pump for injection platform	○	○	○	○	○	○	○	○
下料口温度检测	Temperature detector in material feeding hole	●	●	●	●	●	●	●	●
射移、射胶用线轨	Linear guiders for injection&carriage movement	●	●	●	●	●	●	●	●
双射移油缸	Double-injection shift cylinder	●	●	●	●	●	●	●	●
全封闭保温罩	Totally enclosed heat insulation cover	●	●	●	●	●	●	●	●
加装风冷装置	Installation of air cooling device	○	○	○	○	○	○	○	○
射嘴防护罩	Nozzle shield	●	●	●	●	●	●	●	●
射台表面加花纹板	Carriage covered with anti-slip steel mat	●	●	●	●	●	●	●	●
加装料斗	With Hopper	○	○	○	○	○	○	○	○
带轴承料斗滑动装置	Sliding device of hopper with bearing	○	○	○	○	○	○	○	○
加装磁力架座(配磁力架)	Installation of magnetic frame base (with magnetic frame)	○	○	○	○	○	○	○	○
加大料斗	Enlarged hopper	○	○	○	○	○	○	○	○
埋入式探针射嘴	Embedded probe nozzle	○	○	○	○	○	○	○	○
冷水环增加电磁水阀	Add solenoid water valve for cold water ring	○	○	○	○	○	○	○	○

钣金部分 Metal Plate		TS90	TS130	TS170	TS220	TS260	TS330	TS400	TS470
加宽机门 (双边100mm)	Widened door (100mm on both sides)	○	○	○	○	○	○	○	○
降低安全门高度	Reduce the height of safety door	○	○	○	○	○	○	○	○
同步带电动门	Synchronous with electric door	○	○	○	○	○	○	○	○
锁模区加装滑动上盖板	Installation of top sliding cover plate in mold clamping area	○	○	○	○	○	○	○	○
加装一组6管冷却流量计	Installation of a set of 6-tube cooling flow meters	○	○	○	○	○	○	○	○
运水架 (进 出)配D10快插接头	Water carrier (in and out) with D10 quick connector	○	○	○	○	○	○	○	○
六进六出运水架 (进 出)配D12快插接头	6 in 6 out Water carrier (in and out) with D12 quick connector	●	●	●	●	●	●	●	●

由于技术不断发展、设计的改进及更新，以上规格如有更改，恕不另行通知。
Due to the continuous development of technology, improvement and update of design, the above specifications are subject

液压部分 Hydraulic Part		TS90	TS130	TS170	TS220	TS260	TS330	TS400	TS470
标配一组液压抽芯	Standard 1 set hydraulic core pulling	○	○	○	○	○	○	●	●
一组/二组/三组液压抽芯	Add a / two/three set of hydraulic core pulling system	○	○	○	○	○	○	○	○
一组/二组/三组液压抽芯配快速接头	One / two/three set of hydraulic core pulling system with quick coupling	○	○	○	○	○	○	○	○
一组气动抽芯	One set of pneumatic core pulling system	○	○	○	○	○	○	○	○
一组/二组/三组吹风	One/ two/three set of aeration system	○	○	○	○	○	○	○	○
液压旋转脱模 (不带液压马达)	Hydraulic rotary demoulding (without hydraulic motor)	○	○	○	○	○	○	○	○
液压旋转脱模 (带液压马达)	Hydraulic rotary demoulding (with hydraulic motor)	○	○	○	○	○	○	○	○
顶针/抽芯增加叠加单向阀	Thimble / core pulling system with stacked check valve	○	○	○	○	○	○	○	○
调模刹车液压马达	Hydraulic motor for mold adjustment brake	○	○	○	○	○	○	○	○
开模同步顶针/熔胶/抽芯	Synchronous thimble for mould opening / glue melting / core pulling	○	○	○	○	○	○	○	○
加装射移单向阀	With Carriage movement check valve	●	●	●	●	●	●	●	●
数控背压	CNC back pressure	○	○	○	○	○	○	○	○
液压安全锁	Hydraulic safety lock	○	○	○	○	○	○	○	○
加大一级/二级油泵电机	Upgrade the oil pump motor by a / two grade	○	○	○	○	○	○	○	○
油温预热功能	Oil temperature preheating function	○	○	○	○	○	○	○	○
加大油冷却器	Upgrade oil cooler	○	○	○	○	○	○	○	○
加装冷却水控制阀	Installation of cooling water control valve	○	○	○	○	○	○	○	○
高速伺服注射阀	High speed servo opening and closing valve	○	○	○	○	○	○	○	○
高速伺服开合模阀	High-speed servo open/close die valve	○	○	○	○	○	○	○	○
加装射移单向阀	With Carriage movement check valve	●	●	●	●	●	●	●	●
加装高压软管防爆链	Installation of high pressure hose explosion-proof chain	●	●	●	●	●	●	●	●

电气部分 Electrical Part		TS90	TS130	TS170	TS220	TS260	TS330	TS400	TS470
电动旋转脱模 (不含马达)	Electric rotary demoulding (excluding motor)	○	○	○	○	○	○	○	○
更改地区电压	Changing regional voltage	○	○	○	○	○	○	○	○
加装三色报警灯	Installation of three-color alarm light	●	●	●	●	●	●	●	●
一组2+3 220V/10A插座	One set 2+3 220V/10A power socket	●	●	●	●	●	●	●	●
二组三相32A插座	2 sets 2P 32A power socket	●	●	●	●	●	●	●	●
加装电源插座	Adding power outlets	○	○	○	○	○	○	○	○
配陶瓷发热圈	Equip ceramic heating ring	○	○	○	○	○	○	○	○
加装模具返回确认	Add mould for return confirmation	●	●	●	●	●	●	●	●
射嘴独立控制	Independent nozzle control	●	●	●	●	●	●	●	●
后门急停按钮	Emergency stop button of rear door	●	●	●	●	●	●	●	●
熔胶转速测试装置	Speed test device for glue melting	●	●	●	●	●	●	●	●
油位警报	Oil level alarm	○	○	○	○	○	○	○	○
油温过高报警	Super high oil temperature alarm	●	●	●	●	●	●	●	●
加装电表度	Installation of watt hour meter	○	○	○	○	○	○	○	○
加热用固态继电器	Solid state relay for heating	●	●	●	●	●	●	●	●
热流道接口 (接电脑)	Hot runner interface (connected to computer))	○	○	○	○	○	○	○	○
气辅注射装置接口	Interface of gas assisted injection device	○	○	○	○	○	○	○	○
加装两组模具温控	Add two sets of mould for temperature control	○	○	○	○	○	○	○	○
锁模力检测及显示	Clamping force detection and display	○	○	○	○	○	○	○	○
顺序射胶接口	Sequential glue injection interface	○	○	○	○	○	○	○	○
顺序射胶 (带顺序阀)	Sequential injection (with sequence valve)	○	○	○	○	○	○	○	○
欧规67	European standard 67	○	○	○	○	○	○	○	○
欧规12	European standard 12	○	○	○	○	○	○	○	○

其他部分 Other Part		TS90	TS130	TS170	TS220	TS260	TS330	TS400	TS470
射台表面加花纹板	Pattern plate on the surface of shooting table	●	●	●	●	●	●	●	●
更改钣金颜色 (A/A2以外颜色)	Change metal plate color (color other than A/A2)	○	○	○	○	○	○	○	○

备注: 标准配置 “●” 和备选配置 “○”
Remark:Standard “●” Optional “○”

After-Sale Service

售后服务



快速响应

快速响应客户的需求，收集客户的现场信息并记录故障，给出保养合理化建议；

Fast Response

Quickly respond to customer needs, collect customer site information and record the failure, give reasonable maintenance suggestions;



快速到达

快速到达客户现场，进行设备维修；

Fast Arrival

Quickly arrive at customer site for equipment maintenance;



快速处理

快速处理，帮助客户第一时间将设备调整到最佳状态；

Fast Processing

Quickly processing to help customers adjust the equipment to the best state in the first time;



快速验收


快速完成服务项目验收。

Fast Acceptance

Quickly complete the service project acceptance.

Global Service Net

全球服务网点



Sincerely Appreciate

衷心感谢

超过15000家客户见证并长期支持
Over 15000 customers have witnessed TOPSTAR growth and long supports

