Headquarters and Branch Offices Contacts & Address

Guangdong Topstar Technology Co., Ltd.

ADD: No.35 lianhuan Road, Dalingshan Town, Dongguan City, Guangdong Proxince.

TEL: 0086 769 8305 0999 FAX: 0086 769 8584 5562

E-mail: haiwai@topstarltd.com

Topstar Global R&D Headquarters

ADD: No. 3, Keyuan West 2nd Road, Songshan Lake Park, Dongguan City, Guangdong Province

Topstar Intelligent Equipment Headquarters Base

ADD: No. 39, Lianhuan Road, Lianping Village, Dalingshan Town, Dongguan City, Guangdong Province

East China R&D and Manufacturing Base

ADD: No.1999 Songjia Road, Guoxiang Street, Wuzhong Economic Development Zone, Suzhou City, Jiangsu Province

TEL: 0086-0512-5288 9310 MOB: 185 0156 0757

._____

Topstar (Vietnam) Technology Co.,Ltd.

ADD: No. 48 Kinh Duong Vuong Street, Vu Ninh Ward, Bac Ninh City, Bac Ninh Province
TEL: 0084-346-860 156
MOB: 186 0209 6307

Topstar Mexico Technology S.A DE C.V.

ADD: calle cantu numero 9, interior 103, colonia anzures, delegacion miguel hidalgo, Ciudad de Mexico, Mexico, cp 11590 TEL: 0052-8121728864

Feature and scope of the product does not guarantee the product attributes, only for reference. Our scope of delivery and services provided are based solely on the terms of delivery and services provided are based solely on the terms of the contract. Technical data and illustration are only for reference. We reserve the rights of changing.







haiwai@topstarltd.com www.topstarmachine.com



INJECTION ROBOT PRODUCT SERIES




TSDSC2025-C

www.topstarltd.com



Robot arm selection table







- Add vibration suppression function, which is very suitable for the molding insert project and other high-accuracy product extracting.
 Crosswise axis movement with gear and racks, and the positioning accuracy is higher.

High speed

- Lightweight aluminum alloy arm, reduce 20 structural components, reduce weight by 20%.
- Main arm with lightweight and high-strength A6061 material to improve the overall operating performance.
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the serve drive automatic OFF function, stopped serve motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.
 Posture (C axis) uses cylinder with big cylinder diameter to improve by 20% payload and extract larger

- parts.
 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform

• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Мра	NI/cycle			kg	mm	S	S	N.m	kg
EU-50-60-57 -12TR	AC220 ±10%	1.3	0.5~0.7	2.9	AC Son/o	90°	5	0.05	1.1	5.3	13.2	110~130
EU-50s-60-57 -12TR	0s-60-57 50/60HZ 21 0.5~0.7	0.5~0.7	2.9	Servo Motor	50	5	0.05	1.1	5.3	13.2	120~140	

Outer dimensions



		Model	EL	J-50-60
Unit	: mm	Wodel	EU-50-60-57-12TR	EU-50s-60-57-12TR
А	Total height		1350	1350
В	Total length		1750	1750
С	Traverse stroke		1200	1200
D	Main arm vertical stroke	е	600	600
Е	Main arm standby heigh	t	150	150
F	Effective space for jig mo	bunting	285	285
G	Base internal side to end	l of the box	255	255
Н	Sub-arm vertical stands	у	-	195
1	Main arm max. fwd. mo	vement	580	580
J	Main arm max. crosswi	ise stroke	460	310
K	Main arm min. crosswis	se standby	120	270
L	Min. space between mai	n arm and sub-arm	-	145
М	Sub-arm max. crossw	ise stroke	-	310
Ν	Sub-arm min. crosswis	se standby	-	150
0	Crosswise end to box	end	1095	1095
Р	Min. height of arm after	descending	910	910
0	Jig mounting	Moveable platen	20x50, 4xN	M6 / 30x30, 4xM5
Q	dimension	Fixed platen	20>	x50, 4xM6

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points × 2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
EU-50-60- 57-12TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
EU-50s-60- 57-12TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "●", optional function "O" and "-" indicates none.





- Add vibration suppression function, which is very suitable for the molding insert project and other high-accuracy product extracting.
 Crosswise axis movement with gear and racks, and the positioning accuracy is higher.

High speed

- Lightweight aluminum alloy arm, reduce 20 structural components, reduce weight by 20%.
 Main arm with lightweight and high-strength A6061 material to improve the overall operating performance.
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the servo drive automatic OFF function, stopped servo motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.
 Posture (C axis) uses cylinder with big cylinder diameter to improve by 20% payload and extract larger

- parts.
 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform


• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight	
Unit	V	KW	Мра	NI/cycle	_	_	kg	mm	S	S	N.m	kg	
EU-80-80- 92-14TR		2	0.5~0.7	2.9			6	0.05	1.3	5.6	13.2	260~280	
EU-80-90- 92-16TR	AC220 ±10%	2	0.5~0.7	2.9	AC	0	6	0.05	1.3	5.6	13.2	270~290	
EU-80s-80- 92-14TR	50/60HZ	2.8	0.5~0.7	2.9	Servo Motor	90°	90°	6	0.05	1.3	5.6	13.2	270~290
EU-80s-90- 92-16TR		2.8	0.5~0.7	2.9			6	0.05	1.3	5.6	13.2	280~300	

Outer dimensions





		Model	EU-8	0-80	EU-8	80-90
Uni	t: mm	Wodel	EU-80-80-92-14TR	EU-80s-80-92-14TR	EU-80-90-92-16TR	EU-80s-90-92-16TR
Α	Total height		1650	1650	1770	1770
В	Total length		2060	2060	2240	2240
С	Traverse stroke		1400	1400	1600	1600
D	Main arm vertical	stroke	800	800	900	900
Е	Main arm standby	height	225	225	225	225
F	Effective space for	jig mounting	280	280	280	280
G	Base internal side t	o end of the box	395	395	395	395
Н	Sub-arm vertical s	tandby	-	255	-	255
I	Main arm max. fw	d. movement	900	900	900	900
J	Main arm max. cro	osswise stroke	750	585	750	585
Κ	Main arm min. cro	sswise standby	150	365	150	365
L	Min. space betwee	n main arm and sub-arm	-	230	-	230
М	Sub-arm max. cro	osswise stroke	-	585	-	585
Ν	Sub-arm min. cro	sswise standby	-	135	-	135
0	Crosswise end to	box end	1375	1375	1375	1375
Р	Min. height of arm	after descending	1100	1100	1100	1100
0	Jig mounting	Moveable platen		20x50, 4xM6	30x30, 4xM5	
Q	dimension	Fixed platen		20x50,	4xM6	

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points × 2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
EU-80-80- 92-14TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
EU-80-90- 92-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
EU-80s-80- 92-14TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
EU-80s-90- 92-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "●", optional function "O" and "-" indicates none.





- Add vibration suppression function, which is very suitable for the molding insert project and other high-accuracy product extracting.
 Crosswise axis movement with gear and racks, and the positioning accuracy is higher.

High speed

- Lightweight aluminum alloy arm, reduce 20 structural components, reduce weight by 20%.
 Main arm with lightweight and high-strength A6061 material to improve the overall operating performance.
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the serve drive automatic OFF function, stopped serve motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.
 Posture (C axis) uses cylinder with big cylinder diameter to improve by 20% payload and extract larger

- parts.
 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform

• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle	_	_	kg	mm	S	S	N.m	kg
EUW-80-90- 92-16TR		2	0.5~0.7	2.9			6	0.05	1.2	5.2	13.2	260~280
EUW-80-100 -92-16TR	AC220 ±10%	2	0.5~0.7	2.9	AC	000	6	0.05	1.2	5.2	13.2	270~290
EUW-80s-90 -92-16TR	50/60HZ	2.8	0.5~0.7	2.9	Servo Motor	90°	6	0.05	1.2	5.2	13.2	280~300
EUW-80s-100 -92-16TR		2.8	0.5~0.7	2.9			6	0.05	1.2	5.2	13.2	290~310

Outer dimensions



		Model	EUW-	80-90	EUW-	80-100
Uni	t: mm	Wodel	EUW-80-90-92-16TR	EUW-80s-90-92-16TR	EUW-80-100-92-16TR	EUW-80s-100-92-16TR
Α	Total height		1310	1310	1370	1370
В	Total length		2240	2240	2240	2240
С	Traverse stroke		1600	1600	1600	1600
D	Main arm vertical s	stroke	900	900	1000	1000
Е	Main arm standby h	neight	160	160	160	160
F	Effective space for j	ig mounting	360	360	360	360
G	Base internal side to	end of the box	420	420	420	420
Н	Sub-arm vertical st	andby	-	160	-	160
I	Main arm max. fwo	d. movement	865	865	865	865
J	Main arm max. cro	sswise stroke	690	480	690	480
K	Main arm min. cros	sswise standby	175	385	175	385
L	Min. space between	n main arm and sub-arm	-	210	-	210
М	Sub-arm max. cro	osswise stroke	-	480	-	480
Ν	Sub-arm min. cros	sswise standby	-	110	-	110
0	Crosswise end to I	box end	1290	1290	1290	1290
Р	Min. height of arm	after descending	950	950	950	950
0	Jig mounting	Moveable platen		20x50, 4xM6	/ 30x30,4xM5	
Q	dimension	Fixed platen		20x50	4xM6	

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points × 2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
EUW-80-90- 92-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
EUW-80-100 -92-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
EUW-80s-90 -92-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
EUW-80s-100 -92-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "●", optional function "O" and "-" indicates none.





- Add vibration suppression function, which is very suitable for the molding insert project and other high-accuracy product extracting.
 Crosswise axis movement with gear and racks, and the positioning accuracy is higher.

High speed

- Lightweight aluminum alloy arm, reduce 20 structural components, reduce weight by 20%.
 Main arm with lightweight and high-strength A6061 material to improve the overall operating performance.
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the serve drive automatic OFF function, stopped serve motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.
 Posture (C axis) uses cylinder with big cylinder diameter to improve by 20% payload and extract larger

- parts.
 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform


• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle	_	—	kg	mm	S	S	N.m	kg
EU-120-120- 120-18TR	AC220 ±10%	2	0.5~0.7	3.6	AC Son/o	000	8	0.05	1.5	5.8	20.6	510~530
EU-120s-120- 120-18TR	50/60HZ	2.8	0.5~0.7	3.6	Servo Motor	90°	8	0.05	1.5	5.8	20.6	550~570

Outer dimensions





<u> </u>		Model	EU-12	0–120
Uni	it: mm	Model	EU-120-120-120-18TR	EU-120s-120-120-18TR
Α	Total height		2140	2180
В	Total length		2470	2470
С	Traverse stroke		1800	1800
D	Main arm vertical strok	е	1200	1200
Е	Main arm standby heigh	t	250	250
F	Effective space for jig m	ounting	350	350
G	Base internal side to end	of the box	280	280
Н	Sub-arm vertical standl	Dy	-	300
1	Main arm max. fwd. mo	ovement	1200	1200
J	Main arm max. crossw	ise stroke	1020	780
Κ	Main arm min. crosswi	se standby	175	415
L	Min. space between ma	in arm and sub-arm	-	260
М	Sub-arm max. crossw	ise stroke	-	780
Ν	Sub-arm min. crosswi	se standby	-	120
0	Crosswise end to box	end	1640	1640
Р	Min. height of arm after	descending	1360	1360
0	Jig mounting	Moveable platen	40x50, 6xt	M6
Ų	dimension	Fixed platen	20x50, 4x1	M6

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points × 2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
EU-120-120- 120-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
EU-120s-120- 120-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "●", optional function "O" and "-" indicates none.





- Add vibration suppression function, which is very suitable for the molding insert project and other high-accuracy product extracting.
 Crosswise axis movement with gear and racks, and the positioning accuracy is higher.

High speed

- Lightweight aluminum alloy arm, reduce 20 structural components, reduce weight by 20%.
- Main arm with lightweight and high-strength A6061 material to improve the overall operating performance.
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the serve drive automatic OFF function, stopped serve motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.
 Posture (C axis) uses cylinder with big cylinder diameter to improve by 20% payload and extract larger

- parts.
 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform

• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle	_	_	kg	mm	S	S	N.m	kg
EUW-120-120 -115-18TR		2	0.5~0.7	9.7			8	0.05	1.4	5.6	20.6	500~510
EUW-120-140 -115-18TR	AC220	2	0.5~0.7	9.7	AC	000	8	0.05	1.4	5.6	20.6	510~520
EUW-120s-120 -115-18TR	±10% 50/60HZ	3.1	0.5~0.7	9.7	Servo Motor	90°	8	0.05	1.4	5.6	20.6	540~550
EUW-120s-140 -115-18TR		3.1	0.5~0.7	9.7			8	0.05	1.4	5.6	20.6	550~560

Outer dimensions



		Model	EUW-1	20-120	EUW-1	20 II-140
Unit	: mm	Model	EUW-120-120-115-18TR	EUW-120s-120-115-18TR	EUW-120-140-115-18TR	EUW-120s-140-115-18TR
Α	Total height		1735	1735	1855	1855
В	Total length		2470	2470	2470	2470
С	Traverse stroke		1800	1800	1800	1800
D	Main arm vertical st	roke	1200	1200	1400	1400
Е	Main arm standby he	eight	235	235	235	235
F	Effective space for jig	g mounting	370	370	370	370
G	Base internal side to	end of the box	410	410	410	410
Н	Sub-arm vertical sta	andby	-	285	-	285
I	Main arm max. fwd.	movement	1150	1150	1150	1150
J	Main arm max. cros	sswise stroke	980	780	980	780
K	Main arm min. cros	swise standby	175	375	175	375
L	Min. space between	main arm and sub-arm	-	205	-	205
M	Sub-arm max. cros	sswise stroke	=	780	-	780
Ν	Sub-arm min. cros	swise standby	-	170	-	170
0	Crosswise end to b	ox end	1675	1675	1675	1675
Р	Min. height of arm a	after descending	1505	1505	1505	1505
0	Jig mounting	Moveable platen		40x50	, 6xM6	
Q	dimension	Fixed platen		20x50	, 4xM6	

Note: Same dimensions for positive and negative operation models.

Configuration table

•														
Model	8 independent packaging motion	Free packaging motion(115points ×2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
EUW-120-120 -115-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
EUW-120-140 -115-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
EUW-120s-120 -115-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
EUW-120s-140 -115-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "●", optional function "O" and "-" indicates none.





The main arm with the Q235 material, Stable structure, and High accuracy of repeated positioning, which can meet various non-standard insert motions.

High speed

- Optional imported Domawa motor (rotation speed can reach 6000r/min).
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the servo drive automatic OFF function, stopped servo motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Add the softening function of each axis to prevent robot not picking the products or breaking the arm due to mold opening position changing.
 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.
 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform

• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle		—	kg	mm	S	S	N.m	kg
MDE-50V-60- 57-12TR	AC220 +10%	1.3	0.5~0.7	3.6	AC Servo	90°	3	0.1	1.2	5.4	13.2	160~170
MDE-50sV-60- 57-12TR	±10% 50/60HZ	2.1	0.5~0.7	3.6	Motor	30	3	0.1	1.2	5.4	13.2	180~190

Outer dimensions



	Model	MD	E-50V-60
Unit: mm	Model	MDE-50V-60-57-12TR	MDE-50sV-60-57-12TR
A Total height		1380	1380
B Total length		1730	1730
C Traverse stroke	9	1200	1200
D Main arm vertic	al stroke	600	600
E Main arm standt	by height	185	185
F Effective space to	or jig mounting	270	270
G Base internal sid	le to end of the box	310	310
H Sub-arm vertica	al standby	-	185
Main arm max.	fwd. movement	570	570
J Main arm max.	crosswise stroke	470	320
Main arm min. o	crosswise standby	100	250
_ Min. space betw	een main arm and sub-arm	-	120
VI Sub-arm max.	crosswise stroke	-	320
N Sub-arm min. o	crosswise standby	-	130
O Crosswise end	to box end	1125	1125
Min. height of a	rm after descending	970	970
) Jig mounting	Moveable platen	20x50,4x	xM6/30x30,4xM5
dimension	Fixed platen	20.	X50,4xM6

Note: Same dimensions for positive and negative operation models.

Configuration table

3														
Model	8 independent packaging motion	Free packaging motion(115points × 2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
MDE-50V-60- 57-12TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MDE-50sV-60 -57-12TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function " \bullet ", optional function "O" and "-" indicates none.





The main arm with the Q235 material, Stable structure, and High accuracy of repeated positioning, which can meet various non-standard insert motions.

High speed

- Optional imported Domawa motor (rotation speed can reach 6000r/min).
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the servo drive automatic OFF function, stopped servo motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Add the softening function of each axis to prevent robot not picking the products or breaking the arm
- due to mold opening position changing.

 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.

 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform

• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle		_	kg	mm	S	S	N.m	kg
MDE-80V-80- 79-14TR		1.3	0.5~0.7	2.9			6	0.1	1.3	5.6	13.2	205~215
MDE-80V-90- 91-16TR	AC220 ±10%	1.3	0.5~0.7	2.9	AC	90°	6	0.1	1.3	5.6	13.2	205~215
MDE-80sV-80 -79-14TR	50/60HZ	2.1	0.5~0.7	2.9	Servo Motor	90°	6	0.1	1.3	5.6	13.2	225~235
MDE-80sV-90 -91-16TR		2.1	0.5~0.7	2.9			6	0.1	1.3	5.6	13.2	225~235

Outer dimensions



		Model	MDE-8	30V-80	MDE-8	80V-90
Unit	t: mm	Model	MDE-80V-80-79-14TR	MDE-80sV-80-79-14TR	MDE-80V-90-91-16TR	MDE-80sV-90-91-16TR
Α	Total height		1560	1560	1680	1680
В	Total length		1950	1950	2135	2135
С	Traverse stroke		1400	1400	1600	1600
D	Main arm vertical s	troke	800	800	900	900
Е	Main arm standby h	eight	185	185	185	185
F	Effective space for ji	g mounting	295	295	295	295
G	Base internal side to	end of the box	335	335	335	335
Н	Sub-arm vertical sta	andby	-	210	-	210
1	Main arm max. fwd	. movement	790	790	910	910
J	Main arm max. cros	sswise stroke	700	525	820	640
K	Main arm min. cros	swise standby	90	265	90	270
L	Min. space between	main arm and sub-arm	-	140	-	140
M	Sub-arm max. cro	sswise stroke	-	525	=	640
Ν	Sub-arm min. cros	swise standby	-	125	-	130
0	Crosswise end to b	ox end	1300	1300	1420	1420
Р	Min. height of arm a	after descending	1050	1050	1050	1050
0	Jig mounting	Moveable platen		20x50,4xM6/	30×30,4×M5	
Q	dimension	Fixed platen		20X50	,4xM6	

Note: Same dimensions for positive and negative operation models.

Configuration table

•														
Model	8 independent packaging motion	Free packaging motion(115points ×2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
MDE-80V-80- 79-14TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MDE-80V-90- 91-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MDE-80sV-80 -79-14TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MDE-80sV-90 -91-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "●", optional function "O" and "-" indicates none.





The main arm with the Q235 material, Stable structure, and High accuracy of repeated positioning, which can meet various non-standard insert motions.

High speed

- Optional imported Domawa motor (rotation speed can reach 6000r/min).
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the servo drive automatic OFF function, stopped servo motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
- Built-in dual-system, customer-free choice.
 Add the softening function of each axis to prevent robot not picking the products or breaking the arm.
- due to mold opening position changing.

 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.

 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform

• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Мра	NI/cycle	_	_	kg	mm	S	S	N.m	kg
MEWE-80V-90- 88-14TR		2	0.5~0.7	2.9			6	0.1	1.2	5.2	13.2	200~210
MEWE-80V-90 -88-16TR	AC220 ±10%	2	0.5~0.7	2.9	AC	00%	6	0.1	1.2	5.2	13.2	200~210
MEWE-80sV-90 -88-14TR	50/60HZ	2.8	0.5~0.7	2.9	Servo Motor	90°	6	0.1	1.2	5.2	13.2	220~230
MEWE-80sV-90 -88-16TR		2.8	0.5~0.7	2.9			6	0.1	1.2	5.2	13.2	220~230

Outer dimensions



		Model		MEWE-	80V-90	
Uni	t: mm	Model	MEWE-80V-90-88-14TR	MEWE-80sV-90-88-14TR	MEWE-80V-90-88-16TR	MEWE-80sV-90-88-16TR
Α	Total height		1310	1310	1310	1310
В	Total length		1955	1955	2135	2135
С	Traverse stroke		1400	1400	1600	1600
D	Main arm vertical s	stroke	900	900	900	900
Е	Main arm standby h	neight	195	195	195	195
F	Effective space for	ig mounting	290	290	290	290
G	Base internal side to	end of the box	335	335	335	335
Н	Sub-arm vertical st	andby	-	200	-	200
- 1	Main arm max. fwo	d. movement	880	880	880	880
J	Main arm max. cro	sswise stroke	750	555	750	555
K	Main arm min. cros	sswise standby	130	325	130	325
L	Min. space between	n main arm and sub-arm	-	170	-	170
М	Sub-arm max. cro	osswise stroke	-	555	=	555
Ν	Sub-arm min. cro	sswise standby	-	155	-	155
0	Crosswise end to	box end	1420	1420	1420	1420
Р	Min. height of arm	after descending	905	905	905	905
0	Jig mounting	Moveable platen		20x50,4xM6/	30x30,4xM5	
Q	dimension	Fixed platen		20X50	,4×M6	

Note: Same dimensions for positive and negative operation models.

Configuration table

3														
Model	8 independent packaging motion	Free packaging motion(115points × 2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
MEWE-80V-90 -88-14TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MEWE-80V-90 -88-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MEWE-80sV- 90-88-14TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MEWE-80sV- 90-88-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function " \bullet ", optional function " \circ " and " $\!-$ " indicates none.





The main arm with the Q235 material, Stable structure, and High accuracy of repeated positioning, which can meet various non-standard insert motions.

High speed

- Optional imported Domawa motor (rotation speed can reach 6000r/min).
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the servo drive automatic OFF function, stopped servo motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.

- Built-in dual-system, customer-free choice.
 Add the softening function of each axis to prevent robot not picking the products or breaking the arm.
- due to mold opening position changing.

 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.

 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform

• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Мра	NI/cycle	_	_	kg	mm	S	S	N.m	kg
MEWE-100V-100 -90-16TR		2	0.5~0.7	2.9			8	0.1	1.4	5.6	13.2	260~270
MEWE-100V-120 -96-18TR	AC220 ±10%	2	0.5~0.7	2.9	AC Servo	90°	8	0.1	1.4	5.6	13.2	275~285
MEWE-100sV- 100-90-16TR	50/60HZ	2.8	0.5~0.7	2.9	Motor	90	8	0.1	1.4	5.6	13.2	280~290
MEWE-100sV- 120-96-18TR		2.8	0.5~0.7	2.9			8	0.1	1.4	5.6	13.2	295~305

Outer dimensions



		Model	MEWE-	100V-100	MEWE-	100V-120
Unit	: mm	Model	MEWE-100V-100-90-16TR	MEWE-100sV-100-90-16TR	MEWE-100V-120-96-18TR	MEWE-100sV-120-96-18TR
Α	Total height		1370	1370	1470	1470
В	Total length		2150	2150	2375	2375
С	Traverse stroke		1600	1600	1800	1800
D	Main arm vertical str	oke	1000	1000	1200	1200
Е	Main arm standby hei	ght	215	215	215	215
F	Effective space for jig	mounting	290	290	290	290
G	Base internal side to e	end of the box	375	375	375	375
Н	Sub-arm vertical star	ndby	-	220	-	220
I	Main arm max. fwd. i	movement	900	900	960	960
J	Main arm max. cross	swise stroke	800	570	860	630
K	Main arm min. cross	wise standby	100	330	100	330
L	Min. space between n	nain arm and sub-arm	-	210	-	210
M	Sub-arm max. cross	swise stroke	-	570	-	630
Ν	Sub-arm min. cross	wise standby	-	120	-	120
0	Crosswise end to bo	x end	1480	1480	1540	1540
Р	Min. height of arm af	ter descending	930	930	930	930
0	Jig mounting	Moveable platen		20x50,4xM6/	30x30,4xM5	
Q	dimension	Fixed platen		20X50	,4xM6	

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points ×2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
MEWE-100V- 100-90-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MEWE-100V- 120-96-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MEWE-100sV- 100-90-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MEWE-100sV- 120-96-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "●", optional function "O" and "-" indicates none.





The main arm with the Q235 material, Stable structure, and High accuracy of repeated positioning, which can meet various non-standard insert motions.

High speed

- Optional imported Domawa motor (rotation speed can reach 6000r/min).
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the servo drive automatic OFF function, stopped servo motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Add the softening function of each axis to prevent robot not picking the products or breaking the arm
- due to mold opening position changing.

 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.

 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform

• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Мра	NI/cycle	_	_	kg	mm	S	S	N.m	kg
MDE-120V-120- 97-18TR	AC220 ±10%	2	0.5~0.7	2.9	AC Servo	90° Fixed	6	0.1	1.5	5.7	13.2	270~280
MDE-120sV-120 -97-18TR	50/60HZ	2.8	0.5~0.7	2.9	Motor	30 Tixeu	6	0.1	1.5	5.7	13.2	290~300

Outer dimensions



		Model	MDE-12	20V-120
Uni	it: mm	Model	MDE-120V-120-97-18TR	MDE-120sV-120-97-18TR
Α	Total height		2030	2030
В	Total length		2380	2380
С	Traverse stroke		1800	1800
D	Main arm vertical	stroke	1200	1200
Ε	Main arm standby	neight	210	210
F	Effective space for	jig mounting	295	295
G	Base internal side t	o end of the box	375	375
Н	Sub-arm vertical s	tandby	-	230
- 1	Main arm max. fw	d. movement	970	970
J	Main arm max. cro	osswise stroke	870	695
K	Main arm min. cro	sswise standby	100	275
L	Min. space betwee	n main arm and sub-arm	-	165
М	Sub-arm max. cro	osswise stroke	-	695
Ν	Sub-arm min. cro	sswise standby	-	110
0	Crosswise end to	box end	1540	1540
Р	Min. height of arm	after descending	1080	1080
0	Jig mounting	Moveable platen	20x50,4xM6	/30x30,4xM5
Q	dimension	Fixed platen	20X50),4xM6


Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points × 2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit		Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
MDE-120V-120- 97-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MDE-120sV-120 -97-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function " \bullet ", optional function " \circ " and " –" indicates none.





The main arm with the Q235 material, Stable structure, and High accuracy of repeated positioning, which can meet various non-standard insert motions.

High speed

- Optional imported Domawa motor (rotation speed can reach 6000r/min).
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the servo drive automatic OFF function, stopped servo motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Add the softening function of each axis to prevent robot not picking the products or breaking the arm
- due to mold opening position changing.

 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.

 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform

• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle	_	_	kg	mm	S	S	N.m	kg
MEWE-120V-140 -104-20TR	AC220 ±10%	1.9	0.5~0.7	2.9	AC Servo	90° Fixed	8	0.1	1.4	5.6	13.2	355~365
MEWE-120sV- 140-104-20TR	50/60HZ	2.8	0.5~0.7	2.9	Motor	30 Tixeu	8	0.1	1.4	5.6	13.2	375~385

Outer dimensions



	Model	MEW	E-120V-140
Unit: mm	Wodel	MEWE-120V-140-104-20TR	MEWE-120sV-140-104-20TR
A Total height		1620	1620
B Total length		2560	2560
C Traverse stroke		2000	2000
D Main arm vertical stroke		1400	1400
E Main arm standby height		260	260
Effective space for jig mou	inting	295	295
G Base internal side to end of	of the box	370	370
H Sub-arm vertical standby		-	270
Main arm max. fwd. mov	ement	1040	1040
J Main arm max. crosswis	e stroke	910	680
Main arm min. crosswise	standby	130	360
Min. space between main	arm and sub-arm	-	220
✓ Sub-arm max. crosswis	e stroke	-	680
Sub-arm min. crosswise	standby	-	140
Crosswise end to box er	nd	1615	1615
Min. height of arm after of	lescending	980	980
ر Jig mounting	eable platen	20x50,4>	kM6/30x30,4xM5
dimonsion	d platen	20	X50,4xM6

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points ×2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
MEWE-120V- 140-104-20TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MEWE-120sV- 140-104-20TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function " \bullet ", optional function " \circ " and " –" indicates none.





The main arm with the Q235 material, Stable structure, and High accuracy of repeated positioning, which can meet various non-standard insert motions.

High speed

- Optional imported Domawa motor (rotation speed can reach 6000r/min).
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the servo drive automatic OFF function, stopped servo motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Add the softening function of each axis to prevent robot not picking the products or breaking the arm

- due to mold opening position changing.

 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.

 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform

• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Мра	NI/cycle	_	_	kg	mm	S	S	N.m	kg
MDWE-110-150 -136-20TR		2	0.5~0.7	18			10	0.1	2.8	10.8	49.8	592~693
MDWE-110s-150 -136-20TR	AC 220 ±10% 50/60Hz	2.8	0.5~0.7	27	AC Servo Motor	90°	10	0.1	2.8	10.8	49.8	592~693
MDWE-110-170 -136-20TR	00,00112	2	0.5~0.7	18			10	0.1	2.8	10.8	49.8	592~693

Outer dimensions



		Model	MDWE-	-110–150	MDWE-110-170
Uni	it: mm	Model	MDWE-110-150-136-20TR	MDWE-110s-150-136-20TR	MDWE-110-170-136-25TR
Α	Total height		2080	2080	2200
В	Total length		2730	2730	3210
С	Traverse stroke		2000	2000	2500
D	Main arm vertical strok	Ke .	1500	1500	1700
Е	Main arm standby heigh	nt		290	
F	Effective space for jig m	ounting		330	
G	Base internal side to en	d of the box		480	
Н	Sub-arm vertical stand	by	-	310	-
1	Main arm max. fwd. m	ovement		1360	
J	Main arm max. crossv	vise stroke	1200	980	1200
Κ	Main arm min. crossw	ise standby	160	380	160
L	Min. space between ma	in arm and sub-arm	-	270	-
Μ	Sub-arm max. crossv	vise stroke	-	980	-
Ν	Sub-arm min. crossw	ise standby	-	120	-
0	Crosswise end to box	end	2050	2050	
Р	Min. height of arm afte	rdescending	16	540	1790
0	Jig mounting	Moveable platen		40×50, 6×M8	
Q	dimension	Fixed platen		20×50, 4×M6	

Note: Same dimensions for positive and negative operation models.

Configuration table

•														
Model	8 independent packaging motion	Free packaging motion(115points × 2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
MDWE-110-150 -136-20TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MDWE-110s-150 -136-20TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MDWE-110-170 -136-20TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function " \bullet ", optional function " \circ " and " –" indicates none.





The main arm with the Q235 material, Stable structure, and High accuracy of repeated positioning, which can meet various non-standard insert motions.

High speed

- Optional imported Domawa motor (rotation speed can reach 6000r/min).
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the servo drive automatic OFF function, stopped servo motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Add the softening function of each axis to prevent robot not picking the products or breaking the arm due to mold opening position changing.
 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.
 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform

• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Мра	NI/cycle	_	_	kg	mm	S	S	N.m	kg
MEW-170-170-160 -25TR		2.4	0.5~0.7	26			20	0.2	3.7	13.2	49.8	1210~1260
MEW-170s-170- 160-25TR	AC220 ±10%	3.6	0.5~0.7	26	AC Servo Motor+	90° Fixed	20	0.2	3.7	13.2	49.8	1360~1410
MEW-170-200-160 -30TR	50/60HZ	2.4	0.5~0.7	26	/Air Cylinder		20	0.2	4.2	14.2	49.8	1450~1500
MEW-170s-200- 160-30TR		3.6	0.5~0.7	26			20	0.2	4.2	14.2	49.8	1600~1650





			MEW-1	70-170	MEW-1	70-200
Uni	t: mm	Model	MEW-170-170-160-25TR	MEW-170s-170-160-25TR	MEW-170-200-160-30TR	MEW-170s-200-160-30TR
А	Total height		217	75	22	95
В	Total length		367	20	41	00
С	Traverse stroke		25	00	30	00
D	Main arm vertical st	roke	170	00	20	00
Е	Main arm standby he	eight	37	70	37	70
F	Effective space for jig	mounting	29	95	29	95
G	Base internal side to	end of the box	54	18	37	70
Н	Sub-arm vertical sta	ndby	-	410	-	410
I	Main arm max. fwd.	movement	166	60	16	60
J	Main arm max. cros	swise stroke	1440	1140	1440	1140
K	Main arm min. cross	swise standby	210	510	210	510
L	Min. space between	main arm and sub-arm	-	350	-	350
M	Sub-arm max. cros	sswise stroke	=	1140	-	1140
Ν	Sub-arm min. cross	swise standby	-	170	-	170
0	Crosswise end to be	ox end	24	55	24	55
Р	Min. height of arm a	fter descending	188	80	18	80
0	Jig mounting	Moveable platen		40×50),6xM8	
Q	dimension	Fixed platen		20X50),4xM8	

Note: Same dimensions for positive and negative operation models.

Configuration table

oormgara.														
Model	8 independent packaging motion	Free packaging motion(115points ×2stage)		Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
MEW-170-170- 160-25TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MEW-170s-170 -160-25TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MEW-170-200- 160-30TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MEW-170s-200 -160-30TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "●", optional function "O" and "-" indicates none.





Big payload

- Posture (C axis) uses cylinder with big cylinder diameter to improve payload and extract larger parts.
 The structure of the posture (C axis) is compact, which can ensure taking large products in the moving
- platen.

 With high-power servo driver and motor, the load capacity increases.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Add the softening function of each axis to prevent robot not picking the products or breaking the arm due to mold opening position changing.
 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.
 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.

High stability

Add the vibration suppression function to make machine run more smoothly.
 Use thickened square steel to improve the carrying and stability of traverse axis.


Topstar link application platform

 $\bullet \ \ \text{Real-time remote monitoring, data statistics, analysis and life management of equipment operation.}$

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Мра	NI/cycle			kg	mm	S	S	N.m	kg
MBWE-130-130 -133-20TR	AC220	2.3	0.5~0.7	2.9	AC	90° Fixed	12	0.15	2.7	11	20.6	460
MBWE-130-150 -133-25TR	±10% 50/60HZ	2.3	0.5~0.7	2.9	Servo Motor	90 Fixed	12	0.15	2.7	11.3	20.6	500

Outer dimensions



		Model	MBWE-130-130	MBWE-130-150
Unit: mm	1	Wodel	MBWE-130-130-133-P-20TR	MBWE-130-150-133-P-25TR
A Total	l height		1800	1920
B Total	length		2570	3050
C Trave	erse stroke		2000	2500
D Main	arm vertical stroke		1300	1500
E Main	arm standby height		295	295
F Effect	tive space for jig mounting		-	-
G Base	internal side to end of the box		450	450
H Sub-	arm vertical standby		-	-
l Main	arm max. fwd. movement		1330	1330
J Main	arm max. crosswise stroke		940	940
K Main	arm min. crosswise standby		390	390
L Min. s	space between main arm and si	ub-arm	-	-
M Sub-	-arm max. crosswise stroke		-	-
N Sub-	-arm min. crosswise standby		-	-
O Cross	swise end to box end		1807	1807
P Min. I	height of arm after descending	g	1300	1500
○ Jia m	Moveable	platen		40×50, 6×M6
	nsion Fixed plat	en		20×50, 4×M6

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points × 2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
MBWE-130-130 -133-P-20TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MBWE-130-150 -133-P-25TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "●", optional function "O" and "-" indicates none.





Big payload

- Posture (C axis) uses cylinder with big cylinder diameter to improve payload and extract larger parts.
 The structure of the posture (C axis) is compact, which can ensure taking large products in the moving
- platen.

 With high-power servo driver and motor, the load capacity increases.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Add the softening function of each axis to prevent robot not picking the products or breaking the arm due to mold opening position changing.
 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.
 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.

High stability

Add the vibration suppression function to make machine run more smoothly.
 Use thickened square steel to improve the carrying and stability of traverse axis.


Topstar link application platform

 $\bullet \ \ \text{Real-time remote monitoring, data statistics, analysis and life management of equipment operation.}$

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle		—	kg	mm	S	S	N.m	kg
MBWE-170-170 -182-25TR	AC220 ±10%	2.4	0.5~0.7	24	AC Servo Motor+	90°	20	0.2	2.9	12.2	49.8	1080~1240
MBWE-170-200 -182-30TR	50/60HZ	2.4	0.5~0.7	24	/Air Cylinder	90	20	0.2	3.9	13.2	49.8	1080~1240

Outer dimensions



		Model	MBWE-170-170	MBWE-170-200
Uni	it: mm	oddi	MBWE-170-170-182-25TR	MBWE-170-200-182-30TR
Α	Total height		2160	2280
В	Total length		3270	3750
С	Traverse stroke		2500	3000
D	Main arm vertical stroke	•	1700	2000
Е	Main arm standby height		370	370
F	Effective space for jig mo	unting	-	-
G	Base internal side to end	of the box	495	495
Н	Sub-arm vertical standb	у	-	-
1	Main arm max. fwd. mo	vement	1820	1820
J	Main arm max. crosswi	se stroke	1515	1515
K	Main arm min. crosswis	e standby	305	305
L	Min. space between mair	n arm and sub-arm	-	-
M	Sub-arm max. crosswi	se stroke	-	-
Ν	Sub-arm min. crosswis	e standby	-	-
0	Crosswise end to box e	nd	2345	2345
Р	Min. height of arm after	descending	1915	1915
0	Jig mounting	Moveable platen	40×50, 6×M8	/30×30, 4×M4
Q	dimension	Fixed platen	20×50	, 4×M8

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points × 2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
MBWE-170-170 -182-25TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MBWE-170-200 -182-30TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "●", optional function "O" and "-" indicates none.





The main arm with the Q235 material, Stable structure, and High accuracy of repeated positioning, which can meet various non-standard insert motions.

High speed

- Optional imported Domawa motor (rotation speed can reach 6000r/min).
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

- Total DC bus technology is 10% energy-saving, and the cost of electricity is reduced by 10%.
 Add the servo drive automatic OFF function, stopped servo motor power when robot was standby status, saving 10% of electricity.

High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Add the softening function of each axis to prevent robot not picking the products or breaking the arm due to mold opening position changing.
 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.
 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.


Topstar link application platform


• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle	—	_	kg	mm	S	S	N.m	kg
MBWE-200-200 -230-30TR		4.5	0.5~0.7	48	AC		50	0.2	10	23	181.4	1585~1820
MBWE-200-250 -230-35TR	AC 380 ±10% 50/60Hz	4.5	0.5~0.7	48	Servo Motor+	90°	50	0.2	10	23	181.4	1585~1820
MBWE-200-300 -230-35TR	00,00112	4.5	0.5~0.7	48	Air Cylinder		50	0.2	10	23	181.4	1585~1820

Outer dimensions





	Model		MBWE-200	
Unit: mm		MBWE-200-200-230-30TR	MBWE-200-250-230-35TR	MBWE-200-300-230-35TR
A Total height		2290	2530	2770
B Total length		4040	4520	4520
C Traverse stroke		3000	3500	3500
D Main arm vertical str	oke	2000	2500	3000
E Main arm standby he	ght	210	210	210
F Effective space for jig	mounting	-	-	-
G Base internal side to	end of the box	590	590	590
H Sub-arm vertical sta	ndby	-	-	-
Main arm max. fwd.	movement	2300	2300	2300
J Main arm max. cros	swise stroke	1800	1800	1800
K Main arm min. cross	wise standby	530	530	530
L Min. space between r	nain arm and sub-arm	-	-	-
M Sub-arm max. cros	swise stroke	-	-	-
N Sub-arm min. cross	wise standby	-	-	-
O Crosswise end to be	x end	2960	2960	2960
P Min. height of arm at	ter descending	2020	2530	2530
O Jig mounting	Moveable platen		40×180,8×M8/28×76,4×M6	
dimonoion	Fixed platen		28×76,4×M6	

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points ×2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
MBWE-200-200 -230-30TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MBWE-200-250 -230-35TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
MBWE-200-300 -230-35TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function " \bullet ", optional function "O" and "-" indicates none.





Top needle follow

- Real time adjustment of joint torque
 Make the robotic arm respond smoothly to external forces
 Avoid collision damage to the mold
 Safety: Reduce collision injuries

Motor self-adjusting

- According to actual working conditions, the acceleration and deceleration of the motor can be intelligently adjusted, and the equipment can operate stably and efficiently, increasing efficiency by 30%. Resale of equipment due to scale expansion or technological upgrades, T5 retains its value
 Adaptability: Reduce oscillation and overshoot, able to cope with load and environmental changes

Precision of mold opening

- Automatic and accurate adjustment
 Support injection molding machine call signals, detect the mold opening position of the injection molding machine, and automatically adjust the stroke
 Reduce the number of alarms and machine adjustments caused by inaccurate mold precision Stability: Reduce production fluctuations debugging frequency


Topstar link application platform

 $\bullet \ \ \text{Real-time remote monitoring, data statistics, analysis and life management of equipment operation.}$

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Мра	NI/cycle			kg	mm	S	s	N.m	kg
TMDE-80-80-78 -14TR		1.3	0.5~0.7	2.9			4	0.1	1.4	5.8	13.2	190~210
TMDE-80s-80-78 -14TR	AC220 ±10%	2.1	0.5~0.7	2.9	AC Servo Motor	90°	4	0.1	1.4	5.8	13.2	190~210
TMDE-80-90-78 -16TR	50/60HZ	1.3	0.5~0.7	2.9			4	0.1	1.4	5.8	13.2	190~210
TMDE-80s-90-78 -16TR		2.1	0.5~0.7	2.9			4	0.1	1.4	5.8	13.2	190~210

Outer dimensions



			TMDE	-80-80	TMDE-	-80-90
Uni	t: mm	Model	TMDE-80-80-78-14TR	TMDE-80s-80-78-14TR	TMDE-80-90-78-16TR	TMDE-80s-90-78-16TR
А	Total height		1560	1560	1680	1680
В	Total length		1900	1900	2080	2080
С	Traverse stroke		1400	1400	1600	1600
D	Main arm vertical s	troke	800	800	900	900
Е	Main arm standby h	neight	193	193	193	193
F	Effective space for j	ig mounting	316	316	316	316
G	Base internal side to	end of the box	392	392	392	392
Н	Sub-arm vertical st	andby	-	204	-	204
- 1	Main arm max. fwo	d. movement	780	780	780	780
J	Main arm max. cro	sswise stroke	670	525	670	525
K	Main arm min. cros	sswise standby	110	255	110	255
L	Min. space between	n main arm and sub-arm	-	110	-	110
М	Sub-arm max. cro	sswise stroke	=	525	=	525
Ν	Sub-arm min. cros	sswise standby	-	145	-	145
0	Crosswise end to l	oox end	1360	1360	1360	1360
Р	Min. height of arm	after descending	905	905	905	905
0	Jig mounting	Moveable platen		20x50,4xM6	/30x30,4xM5	
Q	dimension	Fixed platen		20X50),4xM6	

Note: Same dimensions for positive and negative operation models.

Configuration table

3														
Model	8 independent packaging motion	Free packaging motion(115points ×2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
TMDE-80-80- 78-14TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMDE-80s-80 -78-14TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMDE-80-90- 78-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMDE-80s-90 -78-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "ullet", optional function "ullet" and "-" indicates none.



37



Top needle follow

- Real time adjustment of joint torque
 Make the robotic arm respond smoothly to external forces
 Avoid collision damage to the mold
 Safety: Reduce collision injuries

Motor self-adjusting

- According to actual working conditions, the acceleration and deceleration of the motor can be intelligently adjusted, and the equipment can operate stably and efficiently, increasing efficiency by 30%. Resale of equipment due to scale expansion or technological upgrades, T5 retains its value
 Adaptability: Reduce oscillation and overshoot, able to cope with load and environmental changes

Precision of mold opening

- Automatic and accurate adjustment
 Support injection molding machine call signals, detect the mold opening position of the injection molding machine, and automatically adjust the stroke
 Reduce the number of alarms and machine adjustments caused by inaccurate mold precision Stability: Reduce production fluctuations debugging frequency


Topstar link application platform


• Real-time remote monitoring, data statistics, analysis and life management of equipment operation.


Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle	—	_	kg	mm	S	s	N.m	kg
TMEWE-80-90- 76-14TR		2	0.5~0.7	2.9			4	0.1	1.3	5.4	13.2	200~210
TMEWE-80s-90 -76-14TR	AC220	2.8	0.5~0.7	2.9	AC Servo Motor	90°	4	0.1	1.3	5.4	13.2	200~210
TMEWE-80-90- 76-16TR	AC220 ±10%	2	0.5~0.7	2.9			4	0.1	1.3	5.4	13.2	200~210
TMEWE-80s-90 -76-16TR	50/60HZ	2.8	0.5~0.7	2.9			4	0.1	1.3	5.4	13.2	220~230
TMEWE-80-100- 76-16TR		2	0.5~0.7	2.9			4	0.1	1.3	5.4	13.2	220~230
TMEWE-80s-100 -76-16TR		2.8	0.5~0.7	2.9			4	0.1	1.3	5.4	13.2	220~230

Outer dimensions







				TMEWE	-80-90		TMEWE	-80-100
Uni	t: mm	Model	TMEWE-80-90 -76-14TR	TMEWE-80s-90 -76-14TR	TMEWE-80-90 -76-16TR	TMEWE-80s-90 -76-16TR	TMEWE-80-100 -76-16TR	TMEWE-80s-100 -76-16TR
Α	Total height		1260	1260	1260	1260	1320	1320
В	Total length		1900	1900	2080	2080	2080	2080
С	Traverse stroke		1400	1400	1600	1600	1600	1600
D	Main arm vertical	stroke	900	900	900	900	1000	1000
Е	Main arm standby	height	240	240	240	240	240	240
F	Effective space for	jig mounting	270	270	270	270	270	270
G	Base internal side t	to end of the box	392	392	392	392	392	392
Н	Sub-arm vertical s	tandby	-	254	-	254	-	254
-	Main arm max. fw	d. movement	760	760	760	760	760	760
J	Main arm max. cro	osswise stroke	640	420	640	420	640	420
K	Main arm min. cro	sswise standby	120	340	120	340	120	340
L	Min. space betwee	n main arm and sub-arm	-	208	-	208	-	208
М	Sub-arm max. cro	osswise stroke	_	420	-	420	-	420
Ν	Sub-arm min. cro	sswise standby	-	132	-	132	-	132
0	Crosswise end to	box end	1360	1360	1360	1360	1360	1360
Р	Min. height of arm	after descending	905	905	905	905	905	905
0	Jia mountina	Moveable platen			20x50,4xM6	/30x30,4xM5		
Q	dimension	Fixed platen			20X50),4xM6		

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points × 2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO- MAP 67
TMEWE-80- 90-76-14TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMEWE-80s- 90-76-14TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMEWE-80- 90-76-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMEWE-80s- 90-76-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMEWE-80- 100-76-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMEWE-80s- 100-76-16TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function " \bullet ", optional function " \circ " and " $\!-$ " indicates none.





Top needle follow

- Real time adjustment of joint torque
 Make the robotic arm respond smoothly to external forces
 Avoid collision damage to the mold
 Safety: Reduce collision injuries

Motor self-adjusting

- According to actual working conditions, the acceleration and deceleration of the motor can be intelligently adjusted, and the equipment can operate stably and efficiently, increasing efficiency by 30%. Resale of equipment due to scale expansion or technological upgrades, T5 retains its value
 Adaptability: Reduce oscillation and overshoot, able to cope with load and environmental changes

Precision of mold opening

- Automatic and accurate adjustment
 Support injection molding machine call signals, detect the mold opening position of the injection molding machine, and automatically adjust the stroke
 Reduce the number of alarms and machine adjustments caused by inaccurate mold precision Stability: Reduce production fluctuations debugging frequency


Topstar link application platform

 $\bullet \ \ \text{Real-time remote monitoring, data statistics, analysis and life management of equipment operation.}$

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle	_	—	kg	mm	S	S	N.m	kg
TMDE-120-120 -97-18TR	AC220 ±10%	2	0.5~0.7	2.9	AC Servo	90°	6	0.1	1.5	5.7	13.2	270~280
TMDE-120s-120 -97-18TR	50/60HZ	2.8	0.5~0.7	2.9	Motor	50	6	0.1	1.5	5.7	13.2	290~300

Outer dimensions



	Model	ТМ	IDE-120
Unit: mm	model	TMDE-120-120-97-18TR	TMDE-120s-120-97-18TR
A Total height		2030	2030
3 Total length		2380	2380
C Traverse stroke		1800	1800
) Main arm vertical stro	e	1200	1200
E Main arm standby heig	nt	210	210
Effective space for jig n	ounting	295	295
Base internal side to en	d of the box	375	375
H Sub-arm vertical stand	by	-	230
Main arm max. fwd. m	ovement	970	970
J Main arm max. crossv	vise stroke	870	695
Main arm min. crossw	ise standby	100	275
_ Min. space between ma	ain arm and sub-arm	-	165
// Sub-arm max. cross	vise stroke	=	695
Sub-arm min. crossw	ise standby	=	110
) Crosswise end to box	end	1540	1540
Min. height of arm after	rdescending	1080	1080
Jig mounting	Moveable platen	20x50,4xt	M6/30x30,4xM5
dimension	Fixed platen	20>	<50,4xM6

Note: Same dimensions for positive and negative operation models.

Configuration table

o o g u . u .														
Model	8 independent packaging motion	Free packaging motion(115points ×2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rotation unit	EURO- MAP 12	EURO MAP 67
TMDE-120-120 -97-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMDE-120s- 120-97-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function "●", optional function "O" and "-" indicates none.





Top needle follow

- Real time adjustment of joint torque
 Make the robotic arm respond smoothly to external forces
 Avoid collision damage to the mold
 Safety: Reduce collision injuries

Motor self-adjusting

- According to actual working conditions, the acceleration and deceleration of the motor can be intelligently adjusted, and the equipment can operate stably and efficiently, increasing efficiency by 30%. Resale of equipment due to scale expansion or technological upgrades, T5 retains its value
 Adaptability: Reduce oscillation and overshoot, able to cope with load and environmental changes

Precision of mold opening

- Automatic and accurate adjustment
 Support injection molding machine call signals, detect the mold opening position of the injection molding machine, and automatically adjust the stroke
 Reduce the number of alarms and machine adjustments caused by inaccurate mold precision Stability: Reduce production fluctuations debugging frequency


Topstar link application platform

 $\bullet \ \ \text{Real-time remote monitoring, data statistics, analysis and life management of equipment operation.}$

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle	_	_	kg	mm	S	S	N.m	kg
TMEWE-120-120- 96-18TR		2	0.5~0.7	2.9			6	0.1	1.4	5.6	13.2	275~285
TMEWE-120s-120 -96-18TR	AC220 ±10%	2.8	0.5~0.7	2.9	AC Servo Motor	90°	6	0.1	1.4	5.6	13.2	295~305
TMEWE-120-140 -96-18TR	50/60HZ	2	0.5~0.7	2.9		90	6	0.1	1.4	5.6	13.2	295~305
TMEWE-120s-140 -96-18TR		2.8	0.5~0.7	2.9			6	0.1	1.4	5.6	13.2	315~325

Outer dimensions



			TMEWE	-120-120	TMEWE-	-120-140
Uni	t: mm	Model	TMEWE-120-120-96-18TR	TMEWE-120s-120-96-18TR	TMEWE-120-140-96-18TR	TMEWE-120s-140-96-18TR
Α	Total height		1470	1470	1530	1530
В	Total length		2375	2375	2375	2375
С	Traverse stroke		1800	1800	1800	1800
D	Main arm vertical s	stroke	1200	1200	1400	1400
Ε	Main arm standby h	neight	215	215	215	215
F	Effective space for j	ig mounting	290	290	290	290
G	Base internal side to	end of the box	375	375	375	375
Н	Sub-arm vertical st	andby	-	220	-	220
Ι	Main arm max. fwo	d. movement	960	960	960	960
J	Main arm max. cro	sswise stroke	860	630	860	630
Κ	Main arm min. cros	sswise standby	100	330	100	330
L	Min. space between	n main arm and sub-arm	-	210	-	210
М	Sub-arm max. cro	osswise stroke	=	630	=	630
Ν	Sub-arm min. cros	sswise standby	-	120	-	120
0	Crosswise end to b	box end	1540	1540	1540	1540
Р	Min. height of arm	after descending	930	930	930	930
0	Jig mounting	Moveable platen		20x50,4xM6	/30x30,4xM5	
Q	dimension	Fixed platen		20X50	,4xM6	

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	8 independent packaging motion	Free packaging motion(115points ×2stage)	Posture midway descent at release side	Ejector Forward and Backward Coordinated Movement	Defective product reject circuit	Delayed arm descent	Runner release within mold	Start signal of circuit	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	NT gate cutting on crossmember of moving	Rulaliun	EURO- MAP 12	EURO- MAP 67
TMEWE-120- 120-96-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMEWE-120s -120-96-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMEWE-120- 140-96-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0
TMEWE-120s- 140-96-18TR	•	•	•	•	•	•	•	•	•	•	0	0	0	0

Note: Standard function " \bullet ", optional function " \circ " and " - " indicates none.





High performance

- Control system independent research, irregularly-updated software, can be upgraded for life, can be developed and customized according to customer needs.
 Built-in dual-system, customer-free choice.
 Standard RS485 communication interface, Support the MODBUS RTU communication protocol.
 Standard 2 vacuum circuit 2 air circuit function, reserve 11 inputs and 11 outputs.

High speed

- Optional imported whole set of Panasonic servo motors (rotate speed can reach 6000r/min).
 The maximum rotate speed increases 10%, and the accelerate and decelerate time reduced 20%.

High energy-saving effect

Add the servo drive automatic OFF function, stopped servo motor power when robot was standby status, saving 10% of electricity.


Topstar link application platform

 $\bullet \ \mathsf{Real-time} \ \mathsf{remote} \ \mathsf{monitoring}, \ \mathsf{data} \ \mathsf{statistics}, \ \mathsf{analysis} \ \mathsf{and} \ \mathsf{life} \ \mathsf{management} \ \mathsf{of} \ \mathsf{equipment} \ \mathsf{operation}.$

Basic Parameters

Model	Power Supply	Max Power Consumption	Air Pressure	Air Consumption	Drive System	Posture (Air Cylinder)	Max.Load	Repeated Positioning Accuracy	Minimum take-out time	Dry cycle time (excluding fixtures)	Posture Torque	Net Weight
Unit	V	KW	Mpa	NI/cycle	_		kg	mm	S	S	N.m	kg
HDW-80-90- 68-16TR	AC220 ±10% 50/60HZ	2	0.5~0.7	8	AC Servo Motor	90° Fixed	3	0.1	0.7	3.9	6.0	270~290

Outer dimensions



		Model			
	Total height		HDW-80 II-90-68-16TR		
В	Total height		1310		
	Total length		2160		
С	Traverse stroke		1600		
D	Main arm vertical stroke		900		
Е	Main arm standby height		170		
F	Effective space for jig mou	ig mounting 330			
G	Base internal side to end of	f the box	375		
Н	Sub-arm vertical standby		-		
I	Main arm max. fwd. movement		680		
J	Main arm max. crosswis	estroke	500		
Κ	Main arm min. crosswise	standby	180		
L	Min. space between main	arm and sub-arm	-		
Μ	Sub-arm max. crosswis	e stroke	-		
Ν	Sub-arm min. crosswise standby		-		
0	Crosswise end to box end		1170		
Р	Min. height of arm after descending		880		
0	Jig mounting	Moveable platen	40x40, 4xM5 / 30x30, 4xM5		
Q	dimoncion	Fixed platen	20x40, 4xM5		

Note: Same dimensions for positive and negative operation models.

Configuration table

Model	Packaging motion(Max. 256 points)	Free packaging motion(115points ×2stage)	Forward and rotate at removing side	Posture control during traverse		Ejector link	Defective product reject circuit	Initial defective product reject circuit	Start signal of conveyor	Internal memory (for Max 100 molds)	Two language exchange (Chinese/ English)	Additional vacuum sensing unit (4 circuits)	Product gripping 4 circuits	EURO- MAP 12	EURO- MAP 67	Ejector return link
HDW-80-90- 68-16TR	- •	•	•	•	•	•	•	•	•	•	•	0	0	0	0	0

Note: Standard function " \bullet ", optional function " \circ " and " –" indicates none.





Vertical standby position adjustment function with handle.

Adjustment of top and bottom direction of entry position to mold is possible by turning the handle.

Rotation angle adjustment function

• Simple machine adjustment makes it possible to change the direction of rotation and to adjust the rotation angle

Chuck part reversal function

Sprue runner release is performed smoothly by chuck twist


Extraction from fixed & moving side mold

Sprue runner of fixed part mold can be extracted

Basic Parameters


Model	del Power Max Power Supply Consumption Pressure Consumption System	Max Power	Air	Air	Drive	Chuck twist	Max.Load		Net Weight		
Model		Oridok twist	IVIAX.LUAU	Vertical	Crosswise	Swing	rvet weight				
Unit	V	KW	Mpa	NI/cycle	—	_	kg		mm		kg
L-650[V]	AC220V ±10% 50/60HZ	0.1	0.5~0.7	15.1	Air Cylinder	180°	2 [Incl Chuck Weight]	120	650	50~90° [0°Fixed]	30

Outer dimensions



Motion pattern

	Туре 1		Type 2
1	Crosswise advance	1	Crosswise advance
2	Ascent	2	Sprue grip
3	Sprue grip	3	Crosswise retreat
4	Crosswise retreat	4	Retreat
(5)	Retreat	(5)	Swing action
6	Swing action	6	Chuck twist
0	Chuck twist	6	Crosswise advance
7	Crosswise advance	7	Sprue release
8	Sprue release	(8)	Retreat
9	Retreat	9	Swing return
10	Swing return	9	Chuck twist return
10	Chuck twist return	10	Crosswise advance





X-650[V]


Injection Press Range 80-100 ton



Basic Parameters


Model	Power	Max Power Consumption	Air Air Drive Chuck		Chuck twist	Max.Load		Net Weight			
Model	Supply	Consumption	Pressure	Consumption	System	Orluck (Wist	Max.Load	Vertical	Crosswise	Swing	Net Weight
Unit	V	KW	Мра	NI/cycle	—		kg		mm		kg
X-650[V]	AC220V ±10% 50/60HZ	0.1	0.5~0.7	17.7	Air Cylinder	90°	2 【Incl Chuck Weight】	650	120	50~90° [0°Fixed]	52


Outer dimensions



Motion pattern

Type 1	Type 2
① Descent	① Descent
② Crosswise advance	② Product grip
③ Product grip	3 Crosswise retreat
Crosswise retreat	Product release within mold
4 Product release within mold	4 Ascent
⑤ Ascent	⑤ Swing action
6 Swing action	Chuck twist (product side)
Chuck twist (product side)	6 Arm extend
Arm extend	⑦ Product release
8 Product release	Arm retreat
9 Arm retreat	9 Swing return
① Swing return	Chuck twist return (product side)
Chuck twist return(product side)	Crosswise advance








Robot Optional items




C axis



B axis



Servo rotation + flip (AC axis)



Servo rotation + flip (BC axis)



Middle plate sensor



Euromap12




Euromap67




Electric lubricating pump



pump



Longitudinal robot application case



Support pillar application case

CHAPTER OF SERVICE

AFTER-SALE SERVICE

We launched the "4 fast" standard service





Manual lubricating

Fast Response

Quickly respond to customer needs, collect customer site information and record the failure, give reasonable maintenance Suggestions;





Fast Arrival

Quickly arrive at customer site for equipment maintenance;



Fast Processing


Quickly processing to help customers adjust the equipment to the best state in the first time;



Quickly complete the service project acceptance.



Global Service Net



Sincerely Appreciate

Over 15000 customer have witnessed TOPSTAR growth and long supports

